

1 **In the Claims**

2 Claims 10-12 are amended.

3 Claims 1-25 remain in the application and are listed below:

4
5 1. (Previously Presented) A method comprising:

6 receiving a command from a decoder application at an application program
7 interface (API), wherein the API is configured to facilitate the use of a plurality of
8 different multimedia accelerators with the decoder application; and

9 generating one or more filter control command data structures, recognizable
10 by a communicatively coupled accelerator including one or more parameters
11 which, when received by the accelerator, affects one or more filter settings of the
12 accelerator based, at least in part, on the content of the received command.

13
14 2. (Original) A method according to claim 1, further comprising:

15 passing the generated filter control command data structures to the
16 accelerator, wherein the accelerator modifies one or more filter settings in
17 accordance with the parameters embedded within the data structure.

18
19 3. (Original) A method according to claim 1, wherein the filter is a post-
20 processing filter.

21
22 4. (Original) A method according to claim 3, wherein output data
23 subsequent to the application of a post-processing filter are used as prediction
24 references for decoding subsequent data.
25

1
2 5. (Previously Presented) A method according to claim 3, wherein the
3 post-processing filter is one or more of a deblocking filter and a de-ringing filter.
4

5 6. (Original) A method according to claim 1, wherein the parameters
6 include a strength parameter.
7

8 7. (Original) A method according to claim 6, wherein the generated data
9 structure includes a strength parameter for each of one or more block boundaries
10 of a frame.
11

12 8. (Original) A method according to claim 1, wherein the API issues
13 filter control commands for each of a number of edges of luminance and
14 chrominance blocks of received media content.
15

16 9. (Original) A method according to claim 1, wherein the API issues
17 macroblock filter control command data structures for each macroblock of video
18 picture content, each macroblock filter control command comprising four (4) or
19 sixteen (16) luminance block filter control command data structures for controlling
20 the filtering of the luminance blocks of the macroblock, and/or two (2), four (4),
21 eight (8), sixteen (16), or thirty-two (32) chrominance block filter control
22 command data structures for controlling the filtering of the chrominance blocks of
23 the macroblock.
24
25

10. (Currently Amended) One or more computer-readable storage media having computer-readable instructions stored thereon which, when executed by a computer, implement a method according to claim 1.

11. (Currently Amended) A system comprising:
one or more computer-readable media; and
computer-readable instructions on the one or more computer-readable storage media which, when executed by one or more processors, implement a method according to claim 1.

12. (Currently Amended) One or more computer-readable storage media having computer-readable instructions stored thereon which, when executed by a computer, implement an application program interface (API) to dynamically generate one or more filter control command data structures in response to a command received from a decoder application, wherein the one or more filter control command data structure(s) include one or more parameters which, when received by a communicatively coupled accelerator, effect one or more filter settings on the accelerator in accordance with the received command, wherein the API is not specific to any particular multimedia application and/or multimedia accelerator.

13. (Original) A storage medium according to claim 12, wherein the filter control command data structure(s) effect one or more post processing filter(s) of the accelerator.

1 14. (Previously Presented) A storage medium according to claim 12,
2 wherein the filter control command data structure(s) effect one or more of a
3 deblocking filter(s), de-ringing filter(s), and/or another post processing filter of the
4 accelerator.

5
6 15. (Original) A storage medium according to claim 12, wherein the
7 API issues a filter control command data structure for each of a number of edges
8 of luminance and chrominance blocks of received media content.

9
10 16. (Original) A storage medium according to claim 15, wherein the
11 API issues four (4) filter control command data structures for each luminance
12 block, and/or two (2) filter control command data structure(s) for each
13 chrominance block.

14
15 17. (Original) A storage medium according to claim 12, wherein the
16 parameter(s) include a filter strength parameter.

17
18 18. (Previously Presented) A computing system comprising:
19 a decoder application to process received media content; and
20 an operating system including an application program interface (API),
21 support the media processing, wherein the API generates one or more filter control
22 commands including one or more parameters which, when received by a
23 communicatively coupled media processing accelerator, effect one or more filter
24 settings of the accelerator in accordance with a command received from the
25 decoder, wherein the decoder application is configured to iteratively issue

1 configuration commands reflecting various alternative degrees and methods of
2 decoding acceleration capability until choosing one that is acceptable to both the
3 decoder application and the accelerator.

4
5 19. (Original) A computing system according to claim 18, further
6 comprising:

7 one or more media processing accelerator(s), communicatively coupled to
8 the decoder application via the API, including one or more filter(s) responsive to
9 the filter control command data structures reflecting information received in the
10 command from the decoder.

11
12 20. (Original) A computing system according to claim 19, wherein the
13 filter(s) are post processing filters.

14
15 21. (Previously Presented) A computing system according to claim 19,
16 wherein the filter(s) include one or more of a deblocking filter and de-ringing
17 filter.

1 22. (Original) A computing system according to claim 18, wherein the
2 API issues macroblock filter control command data structures for each macroblock
3 of video picture content, each macroblock filter control command comprising four
4 (4) or sixteen (16) luminance block filter control command data structures for
5 controlling the filtering of the luminance blocks of the macroblock, and/or two (2),
6 four (4), eight (8) , sixteen (16) or thirty-two (32) chrominance block filter control
7 command data structures for controlling the filtering of the chrominance blocks of
8 the macroblock.

9
10 23. (Original) A computing system according to claim 18, wherein the
11 filter control command data structures include a strength parameter to control an
12 amount of filter applied by a receiving filter.

13
14 24. (Original) A computing system according to claim 18, further
15 comprising:

16 a storage medium having stored therein a plurality of executable
17 instructions; and

18 an execution unit, coupled to the storage medium, to execute at least a
19 subset of the plurality of executable instructions to implement the operating
20 system and associated API.

21
22 25. (Original) A computing system according to claim 24, wherein the
23 execution unit executes at least a subset of the plurality of executable instructions
24 to implement the decoder application.